



Vcon-ve1-00
structure



Vcon-ve1-00-ext
extension



Module mounting system
minimizing the risk
of deformations



Durable, certified structure
with a galvanized coating



Wind and snow
resistance tests



Dedicated sealing
accessories included
in the set



All mounting components
are made of stainless steel

Compact structure
facilitating transportation



Flexible extension
with additional parking spaces



Adjustable parking
space width



Carport leg/support designed
for internal wiring



Full availability of structural
elements and spare accessories
directly from the manufacturer



More than
energy



EUROPEAN
PRODUCER

Technical specification

The dimensions below refer to the standard carport design – it is possible to adjust the width of the parking space according to individual requirements.






	Vcon-ve1-00	Vcon-ve1-00-ext
	Standard structure for two parking spaces.	Extension of the structure – adding two parking spaces to the standard structure, with the possibility of multiplying them to increase the number of spaces.
Carport structure parameters		
Width [mm]	5750	
Depth [mm]	5470	
Maximum height ⁽¹⁾ [mm]	2800	
Minimum height ⁽¹⁾ [mm]	2030	
Parking space width [mm]	5350	up to 5500 ⁽²⁾
Weight [kg]	800	610
Material	steel S355, hot-dip galvanized, powder coated	
Standard colour ⁽³⁾	grey RAL 7004, structural mat	
Angle of modules ⁽⁴⁾	8°	

⁽¹⁾ Change in structure height upon individual request
⁽²⁾ Dependent on the number of parking spaces in a row
⁽³⁾ The carport structure can be ordered in a custom color
⁽⁴⁾ Change in structure tilt angle upon individual request.

Structural elements included in the set		
	pcs	
Structural post V1 160x80x4x2600 mm	2	1
Structural post V2 160x80x4x2310 mm	2	1
Structural post V3 160x80x4x2210 mm	2	1
Mounting base	2	1
Caps for mounting base (set of 4 pieces)	2	1
Cap nut A2 M20	16	8
Oval washer A2 21 (M20)	16	8
Threaded rod A2 M10x110	12	6
Cap nut A2 M10	24	12
Round washer A2 10,5 (M10)	24	12
Pillar cap	6	3
Allen screw A2 M6x12	24	12
Profile A5 160x80x5x5500 mm	2	0
Profile A8 160x80x8x5500 mm	0	1
Profile B3 100x40x3x5750 mm	9	9
End Cap for profile A5 160x80 mm	4	0
End Cap for profile A8 160x80 mm	0	2
End Cap for profile B3 100x40 mm	18	9
Grip KAB_inox_3 mm	18	9
Allen screw M8x25	36	18
Clamp KPV_inox_1,5 mm	90	90
Push screw M6x16 A2	90	90
Seal 20-30 ⁽⁵⁾ x15x2000 mm	18	21
Connector for B3-profiles	0	9

⁽⁵⁾ Depending on the selected model of PV modules

Compatibility with framed PV modules	
Dimensions of modules - length x width [mm]	1900-2000 x 1100-1140
Additional accessories (available in Avrii Sp. z o.o.)	
Steel brand for Carport Avrii SOL Integra – to be embedded in the foundation	
Components for PV Set – photovoltaic modules, inverter, protections, cabling	
Standards	
CE, FPC Certification	EN 1090-1
elding Process Quality Certificate	EN ISO 3834:2021
Allowed snow and wind load:	
PN-EN 1991-1-3 Eurokod 1	1,6 kN/m²
PN-EN 1991-1-4 Eurokod 1	26 m/s
Warranty	
Standard	10 years
Extended - with Avrii SOL Modules	15 years



Actual dimensions may differ from those specified on the sheet ± 10mm.
The technical sheet contains information valid as of the date specified in the document revision. Due to ongoing research and the introduction of new products, Avrii reserves the right to make any changes to these parameters without prior notice.

Datasheet_EN_AvriiSOL_Integra_Carport_Vcon-ve1-00_Rev.1.1_13_01_2025